

## AMAXX® s receptacle combination

Part no. 960005




- pre-wired for installation
- enclosure and insert made of AMAPLAST

### Technical specifications

|                           |  |
|---------------------------|--|
| CEE 16 A, 5 p, 400 V      | 1  |
| SCHUKO® 16 A, 230 V       | 3  |
| Data port sockets         | 1 Cepex RJ45, 2 fold Cat.6                 |
| Pre-fuse max.             | 16 A                                       |
| InA                       | 16 A                                       |
| Connection / feeder cable | • for 1 cable up to 5 x 10 mm <sup>2</sup> |
| Protection type           | IP 44                                      |
| Shutter                   | false                                      |
| Enclosure material        | Plastic                                    |
| Weight                    | 2190 g                                     |
| Height                    | 650 mm                                     |
| Width                     | 112.5 mm                                   |

### Drawing



Drawing 1 MB 541

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 140 mm |
|                    | IP 67   | 157 mm |
| CEE 16A, 3p, 230V  | IP 44   | 170 mm |
|                    | IP 67   | 169 mm |
| CEE 16A, 5p, 400V  | IP 44   | 172 mm |
|                    | IP 67   | 174 mm |
| CEE 32A, 5p, 400V  | IP 44   | 182 mm |
|                    | IP 67   | 188 mm |

Cable entries: closed for cut out. 1 x M 25 on top and 1 x M 25 on bottom or 1 x M 32 on top and 1 x M 32 on bottom, additionally: 1 x M 20 on top and bottom to cut out.