

AMAXX® receptacle combination

Part no. 970003SI




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover
- with suspension eyes on top, grip hooks on the bottom and chain set provided

Technical specifications

| | |
|---------------------------|--|
| CEE 32 A, 5 p, 400 V | 1 |
| CEE 16 A, 5 p, 400 V | 1 |
| SCHUKO® 16 A, 230 V | 4 |
| Fusing | <ul style="list-style-type: none"> • 1 MCB 32 A, 3 p, C • 1 MCB 16 A, 3 p, C • 4 MCB's 16 A, 1 p, C |
| Pre-fuse max. | 63 A |
| InA | 63 A |
| RDF | 0.85 |
| Connection / feeder cable | • for 1 cable up to 5 x 10 mm ² |
| Protection type | IP 44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 5000 g |
| Height | 260 mm |
| Width | 225 mm |

Drawing



Drawing 1 MB 630

Depth dimensions for identical configuration on both sides.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 282 mm |
| | IP 67 | 326 mm |
| CEE 16A, 3p, 230V | IP 44 | 342 mm |
| | IP 67 | 350 mm |
| CEE 16A, 5p, 400V | IP 44 | 354 mm |
| | IP 67 | 362 mm |
| CEE 32A, 5p, 400V | IP 44 | 372 mm |
| | IP 67 | 382 mm |

Cable entries: closed for cut out.
1 x M 32 on top, 1 x M 25 on top and 1 x M 20 on top.