

## Wall mounted inlet

Part no. 1967



- screw terminals
- external fixing
- one cable entry at top and one blind cable entry (can be cut out) at the back side

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 40-50 V         |
| Clock position            | 12 h            |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 159 g           |
| Declaration of Conformity | EAC, CQC        |

## Drawing

| Drawing<br>2 MB 160   | Amp.<br>Poles | 16  |     | 32  |     |
|---|---------------|-----|-----|-----|-----|
|   |               | 2   | 3   | 2   | 3   |
| Dim. in mm  | a             | 96  | 96  | 96  | 96  |
|   | b             | 73  | 73  | 73  | 73  |
|   | c             | 74  | 74  | 74  | 74  |
|   | d             | 53  | 53  | 53  | 53  |
|   | d1            | 52  | 52  | 52  | 52  |
|   | d2            | 2   | 2   | 2   | 2   |
|   | e             | 62  | 62  | 62  | 62  |
|   | f             | 5.3 | 5.3 | 5.3 | 5.3 |
|   | g             | 8   | 8   | 8   | 8   |
|   | h             | 116 | 116 | 116 | 116 |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 4   | 4   | 4   | 4   |
|   |               | -10 | -10 | -10 | -10 |