

## Plug AM-TOP®

Part no. 21519



- screw terminals
- single part body
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

## Technical specifications

|                           |   |
|---------------------------|---|
| Ampere                    | 32 A  |
| Poles                     | 4 p   |
| Voltage                   | 230 V   |
| Clock position            | 9 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 67   |
| Weight                    | 257 g   |
| Declaration of Conformity | VDE, EAC  |

## Drawing



| Drawing<br>2 MB 218 | Amp.<br>Poles                        | 16   |      |      | 32  |     |     |
|---------------------|--------------------------------------|------|------|------|-----|-----|-----|
|                     |                                      | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm          | a                                    | 142  | 144  | 147  | 186 | 186 | 180 |
|                     | b                                    | 70   | 78   | 87   | 94  | 94  | 101 |
|                     | n                                    | 109  | 111  | 114  | 145 | 145 | 138 |
|                     | y                                    | 14.5 | 16   | 16   | 22  | 22  | 22  |
|                     | Terminal for cond. cross             | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
|                     | section (mm <sup>2</sup> ) min.-max. | -2.5 | -2.5 | -2.5 | -6  | -6  | -6  |