

Phase inverter TM

Part no. 24774




- screw terminals
- highly heat resistant contact carrier • •
- nickel plated contacts with protective cap •
- (form CP)

Technical specifications

Ampere	32 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 67
Weight	400 g
Declaration of Conformity	VDE, EAC

Drawing



Drawing	Amp.	1	6	32	
2 MB 240	Poles	3	5	4	5
Dim. in mm	а	148	153	191	185
	b	70	87	94	101
	h	75	92	97	105
	n	108	112	141	133
	у	14.5	16	22	22
Terminal for cond. cross		1	1	2.5	2.5
section (mm ²) n	ninmax.	-2.5	-2.5	—6	—6
	2 MB 240 Dim. in mm	<u>2 MB 240 Poles</u> Dim. in mm a b h y y	2 MB 240 Poles 3 Dim. in mm a 148 b 70 h 75 n 108 y 14.5	2 MB 240 Poles 3 5 Dim. in mm a 148 153 b 70 87 h 75 92 n 108 112 y 14.5 16	2 MB 240 Poles 3 5 4 Dim. in mm a 148 153 191 b 70 87 94 h 75 92 97 n 108 112 141 y 14.5 16 22 Terminal for cond. cross 1 1 2.5