

## Plug AM-TOP®

Part no. 249




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

## **Technical specifications**

| Ampere                    | 16 A            |
|---------------------------|-----------------|
| Poles                     | 3 p             |
| Voltage                   | 400 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 132 g           |
| Declaration of Conformity | EAC, CQC        |

## Drawing



| Drawing                            | Amp.  | 16    |       |       | 32  |     |      |
|------------------------------------|-------|-------|-------|-------|-----|-----|------|
| 2 MB 217                           | Poles | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm                         | а     | 142   | 147   | 147   | 186 | 186 | 180  |
|                                    | b     | 53    | 59    | 67    | 70  | 70  | 77   |
|                                    | h     | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                                    | n     | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                                    | у     | 14.5  | 16    | 16    | 22  | 22  | 22   |
| Terminal for cond. cross           |       | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
| section (mm <sup>2</sup> ) minmax. |       | -2.5  | -2.5  | -2.5  | —6  | —6  | —6   |