

Industrial Network Distributor

Part no. 25405




- With the new industrial network distributor from the AMAXX® family, MENNEKES offers a product for the expansion of network solutions
- pre-wired for installation
- enclosure front cover electric grey RAL 7035, yellow (GE) RAL 1021 also available on request
- enclosure hinged on the side

Technical specifications

| | |
|---------------------------|--|
| SCHUKO® 16 A, 230 V | 2 |
| Data port sockets | 1 Cepex data port receptacle (black RAL 9005) with 2 RJ45 right angle connector modules for direct connection of patch cables |
| Fitted with | <ul style="list-style-type: none"> • Patch and mounting panel with threaded ground bolt M6 for the optional connection of an external ground conductor |
| Connection / feeder cable | <ul style="list-style-type: none"> • 4 Velcro connectors for fastening installed components on the base plate • 2 screw fittings M 40 with multiple seal, 6 openings for a cable diameter of 6-9 mm including 5 each blanking plugs • 1 screw fitting M 20 • 1 screw set |
| Protection type | IP 44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 4350 g |
| Height | 520 mm |
| Width | 225 mm |

Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 186 mm |
| | IP 67 | 208 mm |
| CEE 16A, 3p, 230V | IP 44 | 216 mm |
| | IP 67 | 220 mm |
| CEE 16A, 5p, 400V | IP 44 | 222 mm |
| | IP 67 | 226 mm |
| CEE 32A, 5p, 400V | IP 44 | 231 mm |
| | IP 67 | 236 mm |
| CEE 63A, 5p, 400V | IP 44 | 260 mm |
| | IP 67 | 260 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.