

Phase inverter plug AM-TOP®

Part no. 319




- screw terminals
- single part body
- cable gland and sealing strain relief and protection against kinking

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 176 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing | Amp. | l | 16 | | | 32 | |
|-----------------------|-----------|-------|--------------|-------|-----|------------|------------|
| 2 MB 217 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 142 | 147 | 147 | 186 | 186 | 180 |
| | b | 53 | 59 | 67 | 70 | 70 | 77 |
| | h | 59 | 69.4 | 76 | 81 | 81 | 89.5 |
| | n | 105.2 | 110.5 | 110.5 | 141 | 141 | 135 |
| | у | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for co | nd. cross | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax. | | -2.5 | — 2.5 | —2.5 | 6 | — 6 | — 6 |
| | | | | | | | |