


Plug PowerTOP plus

Part no. 3325




- highly heat resistant contact carrier
- frame terminals
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

| | |
|---------------------------|---|
| Ampere | 63 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 67 |
| Weight | 848 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing 2 MB 227 | Amp. Poles | 63 | | | 125 | | |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 250 | 250 | 250 | 290 | 290 | 290 |
| | Øb | 111 | 111 | 111 | 128 | 128 | 128 |
| | Øy [max] | 36 | 36 | 36 | 49 | 49 | 49 |
| Terminal for cond. cross | | 6 | 6 | 6 | 25 | 25 | 25 |
| section (mm ²) min.-max. | | -16 | -16 | -16 | -50 | -50 | -50 |