

## Plug PowerTOP®

Part no. 3799




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip

## Technical specifications

| Ampere                    | 16 A  |
|---------------------------|---|
| Poles                     | 3 p   |
| Voltage                   | 400 V   |
| Clock position            | 9 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67   |
| Weight                    | 191 g   |
| Declaration of Conformity | EAC, CQC  |

## Drawing



| Drawing                  | Amp.    |      | 16   |      |      | 32   |      |
|--------------------------|---------|------|------|------|------|------|------|
| 2 MB 171                 | Poles   | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm               | a       | 162  | 172  | 186  | 199  | 199  | 213  |
|                          | b       | 71   | 79   | 89   | 95   | 95   | 102  |
|                          | n       | 129  | 139  | 152  | 157  | 157  | 172  |
|                          | у       | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross |         | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm²) n          | ninmax. | -2.5 | —2.5 | —2.5 | 6    | -6   | -6   |
|                          |         |      |      |      |      |      |      |