

Plug PowerTOP®

Part no. 3935




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip

Technical specifications

Ampere	16 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 44
Weight	241 g
Declaration of Conformity	VDE, EAC, CQC

Drawing



Allip.	ı	10		l	32	
Poles	3	4	5	3	4	5
a	162	172	186	199	199	213
b	54	60	69	72	72	79
h	60	67	77	83	83	91
n	126	136	149	154	154	169
у	19	19	22	24.5	24.5	28.5
. cross	1	1	1	2.5	2.5	2.5
section (mm²) minmax.		— 2.5	— 2.5	-6	— 6	6
	Poles a b h n y	Poles 3 a 162 b 54 h 60 n 126 y 19 l. cross 1	Poles 3 4 a 162 172 b 54 60 h 60 67 n 126 136 y 19 19 l. cross 1 1	Poles 3 4 5 a 162 172 186 b 54 60 69 h 60 67 77 n 126 136 149 y 19 19 22 l. cross 1 1 1	Poles 3 4 5 3 a 162 172 186 199 b 54 60 69 72 h 60 67 77 83 n 126 136 149 154 y 19 19 22 24.5 Loross 1 1 1 1 2.5	Poles 3 4 5 3 4 a 162 172 186 199 199 b 54 60 69 72 72 h 60 67 77 83 83 n 126 136 149 154 154 y 19 19 22 24.5 24.5 L cross 1 1 1 2.5 2.5