

Connector AM-TOP®

Part no. 518




- screw terminals

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 5 p |
| Voltage | 110 V |
| Clock position | 4 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 240 g |
| Declaration of Conformity | EAC, CQC |

Drawing



| Drawing | Amp. | | 16 | | | 32 | |
|--------------------------|-------|------|------|------|-----|-----|-----|
| 3 MB 63 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 162 | 165 | 167 | 209 | 209 | 208 |
| | b | 60 | 68 | 76 | 82 | 82 | 89 |
| | h | 83 | 92 | 98 | 100 | 100 | 108 |
| | у | 14.5 | 16 | 16 | 22 | 22 | 22 |
| | | | | | | | |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax. | | —2.5 | —2.5 | —2.5 | 6 | —6 | 6 |