

**Plug**  
Part no. 655A



- screw terminals
- with cable gland

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 2 p             |
| Voltage                   | 20-25 V         |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 163 g           |
| Declaration of Conformity | EAC             |

**Drawing**



| Drawing<br>2 MB 158   | Amp.<br>Poles | 16   |      | 32   |      |
|---|---------------|------|------|------|------|
|   |               | 2    | 3    | 2    | 3    |
| Dim. in mm  | a             | 150  | 150  | 150  | 150  |
|   | b             | 55   | 55   | 55   | 55   |
|   | h             | 58   | 58   | 58   | 58   |
|   | m             | 128  | 128  | 128  | 128  |
|   | n             | 130  | 130  | 130  | 130  |
|   | y             | 24.7 | 24.7 | 24.7 | 24.7 |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 4    | 4    | 4    | 4    |
|   |               | -10  | -10  | -10  | -10  |