

Wall mounted receptacle

Part no. 7256




- screw terminals
- **X-CONTACT**
- switched
- mechanical DUO-interlock
- circuit breaker, K-characteristics and RCD (0.03A)

Technical specifications

Ampere	32 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Enclosure material	Plastic
Weight	2843 g

Drawing



Drawing	Amp.	16			32		63			
		Poles		3	4	5	4	5	4	5
1 MB 181/620										
Dim. in mm										
a		364	364	364	364	364	460	460		
b		134	134	134	134	134	180	180		
c		160	162	163	168	168	202	202		
d		347	347	347	347	347	440	440		
e		117	117	117	117	117	160	160		
f		6.3	6.3	6.3	6.3	6.3	8.1	8.1		
g		8	8	8	8	8	8	8		
h		391	395	398	408	411	505	505		
M		32/40	32/40	32/40	32/40	32/40	40	40		
M*		2x32	2x32	2x32	2x32	2x32	2x40	2x40		
Max. cable diam. (mm)		27	27	27	27	27	27	27		
Terminal for cond. cross section (mm²) min-max.		1.5	1.5	1.5	2.5	2.5	6	6		
		-4	-4	-4	-10	-10	-25	-25		