

## Wall mounted receptacle

Part no. 7289



- screw terminals
- **X-CONTACT**
- **highly resistant to chemicals**
- highly heat resistant contact carrier
- nickel plated contacts
- switched
- mechanical DUO-interlock
- receptacles can be padlocked

## Technical specifications

|                           |                                       |
|---------------------------|---------------------------------------|
| Ampere                    | 63 A                                  |
| Poles                     | 4 p                                   |
| Voltage                   | 400 V                                 |
| Clock position            | 6 h                                   |
| Hertz                     | 50-60 Hz                              |
| Connection technology     | Screw terminals                       |
| Contact                   | X-CONTACT®                            |
| Protection type           | IP 67                                 |
| Enclosure material        | Plastic, high resistance to chemicals |
| Weight                    | 2526 g                                |
| Declaration of Conformity | EAC, CQC                              |

## Drawing

| Drawing<br>1 MB 180   | Amp.<br>Poles | 63     |        |        |
|---|---------------|--------|--------|--------|
|   |               | 3      | 4      | 5      |
| Dim. in mm  | a             | 260    | 260    | 260    |
|   | b             | 160    | 160    | 160    |
|   | c             | 198    | 198    | 198    |
|   | d             | 240    | 240    | 240    |
|   | e             | 140    | 140    | 140    |
|   | f             | 8.1    | 8.1    | 8.1    |
|   | g             | 8      | 8      | 8      |
|   | h             | 303    | 303    | 303    |
|   | M             | 40     | 40     | 40     |
|   | M*            | 2 x 40 | 2 x 40 | 2 x 40 |
| Max. cable diam. (mm)   |               | 27     | 27     | 27     |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 6      | 6      | 6      |
|   |               | -25    | -25    | -25    |