

Wall mounted receptacle

Part no. 7607




- screw terminals
- for horizontal installation
- switched
- mechanical DUO-interlock receptacles can be padlocked

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 16 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Enclosure material | Plastic |
| Weight | 1320 g |
| Declaration of Conformity | EAC |

Drawing



| Drawing 1 MB 550 Dim. in mm | Amp. Poles | 16 | | | 32 | | |
|-----------------------------------|---------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| a | | 225 | 225 | 225 | 225 | 225 | 225 |
| b | | 168 | 168 | 168 | 168 | 168 | 168 |
| b1 | | 130 | 130 | 130 | 130 | 130 | 130 |
| c | | 80 | 80 | 80 | 80 | 80 | 80 |
| c1 | | 166 | 166 | 166 | 166 | 166 | 166 |
| c2 | | 182 | 183 | 183 | 193 | 193 | 193 |
| d | | 204 | 204 | 204 | 204 | 204 | 204 |
| d1 | | 145 | 145 | 145 | 145 | 145 | 145 |
| e | | 150 | 150 | 150 | 150 | 150 | 150 |
| f | | 7 | 7 | 7 | 7 | 7 | 7 |
| f1 | | Ø7 | Ø7 | Ø7 | Ø7 | Ø7 | Ø7 |
| g | | 8 | 8 | 8 | 8 | 8 | 8 |