

Panel mounted inlet

Part no. 824




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

Technical specifications

| | |
|---------------------------|---|
| Ampere | 63 A |
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 44 |
| Weight | 480 g |
| Declaration of Conformity | EAC, VDE (ÜG) |

Drawing



| Drawing Z MB 155 | Amp. Poles | 63 | | |
|--|---------------|------|------|------|
| | | 3 | 4 | 5 |
| Dim. in mm | a | 110 | 110 | 110 |
| | b | 106 | 106 | 106 |
| | c | 86 | 86 | 86 |
| | d | 90 | 90 | 90 |
| | e | 90 | 90 | 90 |
| | f | 5,5 | 5,5 | 5,5 |
| | g. | 12 | 12 | 12 |
| | g.1 | 2 | 2 | 2 |
| | k | 28 | 28 | 28 |
| | l | 88,5 | 88,5 | 88,5 |
| Terminal for cond. cross section (mm ²) min.-max. | | 6 | 6 | 6 |
| | | -16 | -16 | -16 |