

**Power post**  
Part no. 83685



- from steel tube
- wall thickness 4.5 mm
- electro galvanised
- yellow chromated
- powder-coated
- colour: anthracite (RAL 7016)
- hinged supply aperture
- with safety lock
- dimensions (H x Ø): 1050 x 273 mm (inside)
- weight: approx. 60 kg
- aperture at bottom: (H x W) 60 x 70 mm
- fixing flange: Ø 390 mm
- with 4 fixing holes 15.5 mm
- for fixing to an existing fundament

**Technical specifications**

CEE 32 A, 5 p, 400 V	1
CEE 16 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	2
Fusing	<ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 1 MCB 32 A, 3 p, C</li> <li>• 1 MCB 16 A, 3 p, C</li> <li>• 2 MCB's 16 A, 1 p, B</li> </ul>
Pre-fuse max.	40 A
InA	38 A
RDF	0.6
Connection / feeder cable	<ul style="list-style-type: none"> <li>• for 1 cable up to 5 x 10 mm<sup>2</sup></li> </ul>
Protection type	IP 44
Shutter	false
Enclosure material	Metal
Weight	60000 g
Height	1050 mm
Diameter	273 mm
Declaration of Conformity	EAC

**Drawing**

