

AMAXX® receptacle combination

Part no. 920821




- highly resistant to chemicals made of AMELAN®
- with highly heat resistant contact carrier and nickel plated contacts
- pre-wired for installation
- enclosure front cover grey RAL 7000
- hinged to the side
- fusing behind a transparent cover

Technical specifications

| | |
|---------------------------|--|
| CEE 16 A, 3 p, 230 V | 2 |
| Fusing | • 1 RCD 25 A, 2 p, 0.03 A |
| Pre-fuse max. | 16 A |
| InA | 25 A |
| RDF | 1 |
| Connection / feeder cable | • for 1 cable up to 3 x 10 mm ² |
| Protection type | IP 67 |
| Shutter | false |
| Enclosure material | Plastic, high resistance to chemicals |
| Weight | 2464 g |
| Height | 260 mm |
| Width | 225 mm |
| Declaration of Conformity | EAC |

Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 175 mm |
| | IP 67 | 194 mm |
| CEE 16A, 3p, 230V | IP 44 | 204 mm |
| | IP 67 | 205 mm |
| CEE 16A, 5p, 400V | IP 44 | 209 mm |
| | IP 67 | 213 mm |
| CEE 32A, 5p, 400V | IP 44 | 221 mm |
| | IP 67 | 227 mm |
| CEE 63A, 5p, 400V | IP 44 | 248 mm |
| | IP 67 | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.