

## AMAXX® receptacle combination

Part no. 941265




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- MENNEKES AMAXX® receptacle combination for camp sites already comply to the standard and regulations which came into force 01.07.2007 according to DIN VDE 0100-708\_2006-02 and DIN VDE 0100-754:2006-02

## Technical specifications

CEE 16 A, 3 p, 230 V	4	
Fusing		<ul style="list-style-type: none"> <li>• 4 RCD's 25 A, 2 p, 0.03 A</li> <li>• 4 MCB's 16 A, 1 p, B</li> </ul>
Pre-fuse max.	63 A	
InA	32 A	
RDF	1	
Connection / feeder cable		<ul style="list-style-type: none"> <li>• for 2 cables up to 5 x 25 mm<sup>2</sup></li> </ul>
Protection type	IP 44	
Shutter	false	
Enclosure material	Plastic	
Weight	5986 g	
Height	520 mm	
Width	225 mm	

## Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	186 mm
	IP 67	208 mm
CEE 16A, 3p, 230V	IP 44	216 mm
	IP 67	220 mm
CEE 16A, 5p, 400V	IP 44	222 mm
	IP 67	226 mm
CEE 32A, 5p, 400V	IP 44	231 mm
	IP 67	236 mm
CEE 63A, 5p, 400V	IP 44	260 mm
	IP 67	260 mm

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.