

## AMAXX® s receptacle combination

Part no. 960001




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

### Technical specifications

|                           |   |
|---------------------------|---|
| SCHUKO® 16 A, 230 V       | 3   |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 3 MCB's 16 A, 1 p, C</li> </ul> |
| Pre-fuse max.             | 63 A  |
| InA                       | 16 A  |
| RDF                       | 1   |
| Connection / feeder cable | <ul style="list-style-type: none"> <li>• for 1 cable up to 5 x 10 mm<sup>2</sup></li> </ul>                 |
| Protection type           | IP 44   |
| Shutter                   | false   |
| Maximum current load      | up to max. 100 A permissible total current  |
| Enclosure material        | Plastic   |
| Weight                    | 3420 g  |
| Height                    | 650 mm  |
| Width                     | 112.5 mm  |
| Declaration of Conformity | EAC   |

### Drawing



**Drawing 1 MB 541**

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 140 mm |
|                    | IP 67   | 157 mm |
| CEE 16A, 3p, 230V  | IP 44   | 170 mm |
|                    | IP 67   | 169 mm |
| CEE 16A, 5p, 400V  | IP 44   | 172 mm |
|                    | IP 67   | 174 mm |
| CEE 32A, 5p, 400V  | IP 44   | 182 mm |
|                    | IP 67   | 188 mm |

Cable entries: closed for cut out. 1 x M 25 on top and 1 x M 25 on bottom or 1 x M 32 on top and 1 x M 32 on bottom, additionally: 1 x M 20 on top and bottom to cut out.