

## AMAXX® s receptacle combination

Part no. 960018




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

## Technical specifications

CEE 16 A, 5 p, 400 V	1
French/Belgian standard	3
Fusing	• 1 RCD 40 A, 4 p, 0.03 A
Pre-fuse max.	16 A
InA	16 A
RDF	1
Connection / feeder cable	• for 1 cable up to 5 x 10 mm <sup>2</sup>
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	3330 g
Height	650 mm
Width	112.5 mm
Declaration of Conformity	EAC

## Drawing



Drawing 1 MB 541

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	140 mm
	IP 67	157 mm
CEE 16A, 3p, 230V	IP 44	170 mm
	IP 67	169 mm
CEE 16A, 5p, 400V	IP 44	172 mm
	IP 67	174 mm
CEE 32A, 5p, 400V	IP 44	182 mm
	IP 67	188 mm

Cable entries: closed for cut out. 1 x M 25 on top and 1 x M 25 on bottom or 1 x M 32 on top and 1 x M 32 on bottom, additionally: 1 x M 20 on top and bottom to cut out.