

**Plug AM-TOP®**

Part no. 2184




- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

**Technical specifications**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 3 p             |
| Voltage               | 50-250 V        |
| Clock position        | 3 h             |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP44            |
| Weight                | 131 g           |
| Certifications        | VDE, EAC, CQC   |

**Drawing**



| Drawing<br>2 MB 217                  | Amp.<br>Poles | 16    |       |       | 32  |     |      |
|--------------------------------------|---------------|-------|-------|-------|-----|-----|------|
|                                      |               | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm                           | a             | 142   | 147   | 147   | 186 | 186 | 180  |
|                                      | b             | 53    | 59    | 67    | 70  | 70  | 77   |
|                                      | h             | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                                      | n             | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                                      | y             | 14.5  | 16    | 16    | 22  | 22  | 22   |
| Terminal for cond. cross             |               | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5  | -2.5  | -2.5  | -6  | -6  | -6   |