

AMAXX receptacle combination

Part no. 930020




- pre-wired for installation
- hinged to the side
- enclosure and insert made of **AMAPLAST**
- fusing behind a transparent cover

Technical specifications

| | |
|---------------------------|---|
| CEE 32 A, 5 p, 400 V | 1 |
| CEE 16 A, 5 p, 400 V | 1 |
| CEE 16 A, 3 p, 230 V | 2 |
| SCHUKO® | 1 |
| Fusing | <ul style="list-style-type: none"> • 1 RCD 40 A, 4 p, 0.03 A • 1 MCB 16 A, 3 p, C • 3 MCB's 16 A, 1 p, C |
| Pre-fuse max. | 32 A |
| InA | 32 A |
| RDF | 0.75 |
| Connection / feeder cable | <ul style="list-style-type: none"> • for 2 cables up to 5 x 25 mm² |
| Protection type | IP44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 5740 g |
| Height | 390 mm |
| Width | 225 mm |

Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|-------------------|---------|--------|
| SCHUKO®16A, 230 V | IP 44 | 175 mm |
| | IP 67 | 194 mm |
| CEE 16A, 3p, 230V | IP 44 | 204 mm |
| | IP 67 | 205 mm |
| CEE 16A, 5p, 400V | IP 44 | 209 mm |
| | IP 67 | 213 mm |
| CEE 32A, 5p, 400V | IP 44 | 221 mm |
| | IP 67 | 227 mm |
| CEE 63A, 5p, 400V | IP 44 | 248 mm |
| | IP 67 | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.