

## Cepex wall mounted receptacle SCHUKO®, grey

Part no. 4976




- grey
- screw terminals
- with labelling field
- with safety lock
- two keys
- cannot be dismantled when locked
- on request with identical lock
- cable entry: 1 x M 25 with cable gland at top, 1 x M 25 to be cut out at the bottom, 1 x M 20 to be cut out at the back side, for cables 7 up to 13 mm Ø
- with identical lock: part no + index G

### Technical specifications

Ampere	16 A
Poles	2 p+PE
Voltage	230 V
Hertz	50-60 Hz
Protection type	IP44
Shutter	false
Weight	275 g

### Drawing



Drawing 1 MB 313 Dim. in mm	Amp. Poles	16			32		
		3	4	5	3	4	5
a		93	93	93	93	93	93
b		90	90	90	90	90	90
c		90	90	90	102	102	102
d		75	75	75	75	75	75
e		73	73	73	73	73	73
f		5.5	5.5	5.5	5.5	5.5	5.5
g		4.2	4.2	4.2	4.2	4.2	4.2
k		36	36	36	36	36	36
y		25.5	25.5	25.5	25.5	25.5	25.5
M		25x1.5	25x1.5	25x1.5	25x1.5	25x1.5	25x1.5
Terminal for cond. cross section (mm²) min.-max.		1.5	1.5	1.5	2.5	2.5	2.5
		-4	-4	-4	-6	-6	-6