

# Panel mounted inlet

Part number: 75316



**MENNEKES**  
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1  
57399 Kirchhundem  
GERMANY

[www.MENNEKES.org](http://www.MENNEKES.org)

## Product Description

- highly heat resistant contact carrier, nickel plated contacts
- external fixing
- 15° inclination
- EcoLine
- aluminium enclosure
- seawater resistant products are available on request

## Technical Details

Panel mounted inlet	75316
Ampere	200A
Number of poles	5p
Clock position	6h
Nominal voltage AC	400V
Nominal frequency	50 - 60 Hz
Protection type IP	IP67
Contact carrier	highly heat resistant contact carrier, nickel plated contacts
Connection	cage terminals
Tightening torque connection terminal	allen key
Phase inverter	without phase inverter
Pilot contact	2 pilot contacts
Flange dimensions	140 x 140 mm
Hole spacings	120 x 120 mm
Insertion direction	angled
Inclination	15°
Type of mounting	external fixing
Military version	no
Protection cap	without protection cap
Tightening torque connection terminal	8 Nm
Recommended wire end treatment for supply cable connection terminal	usable with and without ferrule
Strip length jacket	150 mm
Strip length conductor	30 mm
Conductor cross-section min.	35 mm <sup>2</sup>

<b>Panel mounted inlet</b>	<b>75316</b>
Conductor cross-section max.	150 mm <sup>2</sup>
Conductor cross-section pilot max.	4 mm <sup>2</sup>
Weight (net)	3340 g
Packaging unit	1 Stück
Quantity per pallet	54 Stück
EAN / identification number	4015394283164

<b>Permissible ambient conditions</b>		
	Min.	Max.
Permanent ambient temperature	-40 °C	100 °C

<b>Material properties</b>	
Housing	aluminium grey [no RAL colour code]

**Material resistance**

The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.

<b>Material and environmental properties</b>	
RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓
Halogen-free	yes

<b>Regulations and Standards</b>	
Norm	DIN EN IEC 60309
Declaration of Conformity	CE

# Dimensional Drawing

Drawing  
2 MB 247

Dim. in mm

