

Connector TM

Part no. 24885




- screw terminals
- frame terminals
- rubberised grip area
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides (form DS)

Technical specifications

Ampere	[63.0, 63.0] A
Poles	[5.0, 5.0] p
Voltage	400-400 V
Clock position	[6.0, 6.0] h
Hertz	50-60, 50-60 Hz
Connection technology	[ClassificationAttributeValueModel (8796126970464@8), ClassificationAttributeValueModel (8796126970464@8)]
Contact	nickel plated contacts, highly heat resistant contact carrier, X-CONTACT®, highly heat resistant contact carrier, nickel plated contacts, X-CONTACT®
Protection type	[ClassificationAttributeValueModel (8796126741088@33), ClassificationAttributeValueModel (8796126741088@33)]
Weight	880 g
Declaration of Conformity	DE, VDE

Drawing



Drawing 3 MB 68	Amp. Poles	63			125		
		3	4	5	3	4	5
Dim. in mm	a	270	270	270	310	310	310
	b	113	113	113	125	125	125
	h	123	123	123	135	135	135
	y	36	36	36	49	49	49
Terminal for cond. cross		6	6	6	25	25	25
section (mm ²) min.-max.		-16	-16	-16	-50	-50	-50