

Connector TM

Part no. 24985




- screw terminals
- frame terminals
- rubberised grip area
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides (form DS)

Technical specifications

| | |
|---------------------------|---|
| Ampere | 125 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | X-CONTACT®, nickel plated contacts, highly heat resistant contact carrier |
| Protection type | IP 67 |
| Weight | 1400 g |
| Declaration of Conformity | DE, VDE, CN, CQC |

Drawing



| Drawing 3 MB 68 | Amp. Poles | 63 | | | 125 | | |
|--------------------|--------------------------------------|-----|-----|-----|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 270 | 270 | 270 | 310 | 310 | 310 |
| | b | 113 | 113 | 113 | 125 | 125 | 125 |
| | h | 123 | 123 | 123 | 135 | 135 | 135 |
| | y | 36 | 36 | 36 | 49 | 49 | 49 |
| | Terminal for cond. cross | 6 | 6 | 6 | 25 | 25 | 25 |
| | section (mm ²) min.-max. | -16 | -16 | -16 | -50 | -50 | -50 |