

Plug AM-TOP®

Part no. 283



- screw terminals


•

- single part body cable gland and sealing strain relief and protection against kinking

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Weight | 165 g |
| Declaration of Conformity | DE,VDE, CN,CQC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | |
|------------------------------------|-------|------|------|------|-----|-----|-----|
| 2 MB 218 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | а | 142 | 144 | 147 | 186 | 186 | 180 |
| | b | 70 | 78 | 87 | 94 | 94 | 101 |
| | n | 109 | 111 | 114 | 145 | 145 | 138 |
| | У | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm ²) minmax. | | -2.5 | -2.5 | —2.5 | —6 | —6 | —6 |