


## Wall mounted phase inverter inlet

Part no. 3345



- screw terminals

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 4 p             |
| Voltage                   | 230 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 399 g           |
| Declaration of Conformity | DE,VDE          |

## Drawing



| Drawing<br>2 MB 32  | Amp.<br>Poles | 16                         |      |      | 32                         |       |       |
|---|---------------|----------------------------|------|------|----------------------------|-------|-------|
|   |               | 3                          | 4    | 5    | 3                          | 4     | 5     |
| Dim. in mm  | a             | 87                         | 100  | 100  | 128                        | 128   | 128   |
|   | b             | 64                         | 75   | 75   | 84                         | 84    | 84    |
|   | c             | 93                         | 106  | 110  | 133                        | 133   | 135   |
|   | d             | 40                         | —    | —    | —                          | —     | —     |
|   | d1            | —                          | 10,5 | 10,5 | 11                         | 11    | 11    |
|   | e             | 50,5                       | 59   | 59   | 68                         | 68    | 68    |
|   | f             | 4,5                        | 5    | 5    | 5,3                        | 5,3   | 5,3   |
|   | g             | 4                          | 4    | 4    | 4                          | 4     | 4     |
|   | h             | 122                        | 133  | 135  | 169                        | 169   | 170   |
|   | M             | 20                         | 20   | 20   | 32                         | 32    | 32    |
|   | M*            | 1x20 (blind) to be cut out |      |      | 2x25 (blind) to be cut out |       |       |
| Max. cable diam. (mm)   |               | 15                         | 15   | 15   | 18/25                      | 18/25 | 18/25 |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 1                          | 1    | 1    | 2,5                        | 2,5   | 2,5   |
|   |               | -2,5                       | -2,5 | -2,5 | -6                         | -6    | -6    |