

Panel mounted phase inverter inlet

Part no. 3348



- screw terminals
- with hinged lid

Technical specifications

| Ampere | 16 A |
|---------------------------|-----------------|
| Poles | 4 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 210 g |
| Declaration of Conformity | DE,VDE |

Drawing



| 2 MB 43 | Poles | 4 | 5 | 3 | 4 | 5 |
|--------------------------|--------|------|------|-----|-----|-----|
| Dim. in mm | a | 85 | 85 | 75 | 75 | 75 |
| | b | 85 | 85 | 90 | 90 | 90 |
| | c | 104 | 106 | 115 | 115 | 117 |
| | d | 64 | 64 | 45 | 45 | 45 |
| | d1 | 10 | 10 | 13 | 13 | 13 |
| | e | 64 | 64 | 78 | 78 | 78 |
| | f | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| | g. | 27 | 27 | 27 | 27 | 27 |
| | g.1 | 2 | 2 | 1 | 1 | 1 |
| | h | 140 | 140 | 150 | 150 | 150 |
| | - 1 | 50 | 50 | 55 | 55 | 55 |
| Terminal for cond. cross | | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) m | inmax. | —2.5 | -2.5 | 6 | -6 | 6 |