

**Plug PowerTOP®**

Part no. 3925



- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip

**Technical specifications**

|                           |   |
|---------------------------|---|
| Ampere                    | 16 A  |
| Poles                     | 4 p   |
| Voltage                   | 110 V   |
| Clock position            | 4 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 44   |
| Weight                    | 198 g   |
| Declaration of Conformity | DE,VDE  |

**Drawing**



| Drawing<br>2 MB 174                  | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------------------|---------------|------|------|------|------|------|------|
|                                      |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm                           | a             | 162  | 172  | 186  | 199  | 199  | 213  |
|                                      | b             | 54   | 60   | 69   | 72   | 72   | 79   |
|                                      | h             | 60   | 67   | 77   | 83   | 83   | 91   |
|                                      | n             | 126  | 136  | 149  | 154  | 154  | 169  |
|                                      | y             | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross             |               | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5 | -2.5 | -6   | -6   | -6   |