

## Connector PowerTOP®

Part no. 3964



- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

## Technical specifications

|                           |                                       |
|---------------------------|---------------------------------------|
| Ampere                    | 16 A                                  |
| Poles                     | 5 p                                   |
| Voltage                   | 400 V                                 |
| Clock position            | 6 h                                   |
| Hertz                     | 50-60 Hz                              |
| Connection technology     | Screw terminals                       |
| Contact                   | highly heat resistant contact carrier |
| Protection type           | IP 44                                 |
| Weight                    | 279 g                                 |
| Declaration of Conformity | CN,CQC                                |

## Drawing



| Drawing<br>3 MB 51/3                 | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------------------|---------------|------|------|------|------|------|------|
|                                      |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm                           | a             | 165  | 180  | 190  | 214  | 214  | 223  |
|                                      | b             | 60   | 68   | 76   | 82   | 82   | 89   |
|                                      | h             | 76   | 84   | 90   | 92   | 92   | 99   |
|                                      | y             | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross             |               | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5 | -2.5 | -6   | -6   | -6   |