

**Plug**  
Part no. 636A




- screw terminals with grommet

**Technical specifications**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 3 p             |
| Voltage               | 20-25 V         |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Weight                | 153 g           |

**Drawing**



| Drawing<br>2 MB 159                  | Amp.<br>Poles | 16  |     | 32  |     |
|--------------------------------------|---------------|-----|-----|-----|-----|
|                                      |               | 2   | 3   | 2   | 3   |
| Dim. in mm                           | a             | 130 | 130 | 130 | 130 |
|                                      | b             | 55  | 55  | 55  | 55  |
|                                      | h             | 58  | 58  | 58  | 58  |
|                                      | m             | 108 | 108 | 108 | 108 |
|                                      | n             | 107 | 107 | 107 | 107 |
|                                      | y             | 25  | 25  | 25  | 25  |
|                                      | z             | 9   | 9   | 9   | 9   |
| Terminal for cond. cross             |               | 4   | 4   | 4   | 4   |
| section (mm <sup>2</sup> ) min.-max. |               | -10 | -10 | -10 | -10 |