

## Wall mounted receptacle

Part no. 7021




- screw terminals
- X-CONTACT®
- contactor and electrical PCS interlock

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 63 A            |
| Poles                     | 4 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | X-CONTACT®      |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 3150 g          |
| Declaration of Conformity | CN,CQC          |

## Drawing



| Drawing   | Amp.  | 63   |      |
|---|-------|------|------|
| 1 MB 178  | Poles | 4    | 5    |
| Dim. in mm  | a     | 264  | 264  |
|   | b     | 163  | 163  |
|   | c     | 191  | 191  |
|   | d     | 240  | 240  |
|   | e     | 140  | 140  |
|   | f     | 8.1  | 8.1  |
|   | g     | 8    | 8    |
|   | h     | 319  | 319  |
|   | M     | 2x40 | 2x40 |
|   | M*    | 2x40 | 2x40 |
| Max. cable diam. (mm)   |       | 27   | 27   |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |       | 6    | 6    |
|   |       | -25  | -25  |