

## Wall mounted receptacle

Part no. 7130




- screw terminals
- with DIN rail, optional fitting of Neozed, Diazed, circuit-breakers and RCD's

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 988 g           |
| Declaration of Conformity | CN,CQC          |

## Drawing



| Drawing<br>1 MB 378   | Amp.<br>Poles | 16            |      |      | 32            |      |
|---|---------------|---------------|------|------|---------------|------|
|   |               | 3             | 4    | 5    | 4             | 5    |
| Dim. in mm  | a             | 225           | 225  | 225  | 225           | 225  |
|   | b             | 118           | 118  | 118  | 118           | 118  |
|   | c             | 144           | 146  | 147  | 152           | 153  |
|   | d             | 208           | 208  | 208  | 208           | 208  |
|   | e             | 101           | 101  | 101  | 101           | 101  |
|   | f             | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  |
|   | g             | 8             | 8    | 8    | 8             | 8    |
|   | h             | 252           | 255  | 259  | 268           | 274  |
|   | M             | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |
|   | M*            | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 |
| Max. cable diam. (mm)   |               | 25            | 25   | 25   | 25            | 25   |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  |
|   |               | -4            | -4   | -4   | -10           | -10  |