

Wall mounted receptacle

Part no. 7606






Technical specifications

| Ampere | 16 A |
|-----------------------|-----------------|
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Enclosure material | Plastic |
| Weight | 1308 g |

Drawing



| Drawing | Amp. | | 16 | | | 32 | |
|------------|-------|-----|-----|-----|-----|-----|-----|
| 1 MB 550 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 225 | 225 | 225 | 225 | 225 | 225 |
| | b | 168 | 168 | 168 | 168 | 168 | 168 |
| | b1 | 130 | 130 | 130 | 130 | 130 | 130 |
| | c | 80 | 80 | 80 | 80 | 80 | 80 |
| | c1 | 166 | 166 | 166 | 166 | 166 | 166 |
| | c2 | 182 | 183 | 183 | 193 | 193 | 193 |
| | d | 204 | 204 | 204 | 204 | 204 | 204 |
| | d1 | 145 | 145 | 145 | 145 | 145 | 145 |
| | e | 150 | 150 | 150 | 150 | 150 | 150 |
| | f | 7 | 7 | 7 | 7 | 7 | 7 |
| | f1 | Ø7 | Ø7 | Ø7 | Ø7 | Ø7 | Ø7 |
| | g | 8 | 8 | 8 | 8 | 8 | 8 |
| | • | 1 | | | 1 | | |